

NP510A

TECHNICAL DATA BULLETIN

GRADE: NP510A

NEMA LI 1-1998 Grade: FR-4

U.L. LISTED: Y²

DESCRIPTION: NP510A is a woven glass fabric composite combined with epoxy resin system. This material contains bromine on the epoxy resin backbone. NP510A is certifiable to MIL-I-24768/27, Type GEE-F, ANSI/NEMA IM 60000-2021 Grade FR-4, IEC 60893-3-2 PE GC 202, ASTM D709 Type FR-4 and IPC 4101/21.

TYPICAL PROPERTIES

		UNITS	VALUE		
			Thickness Tested		
			0.0625"	0.125"	0.500"
PHYSICAL PROPERTIES					
Specific Gravity (ASTM D792)		-			1.85
Rockwell Hardness (ASTM D785)	0.250" Build-up	M Scale	98		
Moisture Absorption (ASTM D570)	Condition D ₁ -24/23	%	0.10		
Flexural Strength (ASTM D790)	Condition A LW / CW	psi (MPa)	65,000 / 52,000 (448.2) / (358.5)		
Flexural Modulus (ASTM D790)	Condition A LW / CW	kpsi (GPa)	2,900 / 2,600 (20.0) / (17.9)		
Tensile Strength (ASTM D638)	Condition A LW / CW	psi (MPa)	40,000 / 32,000 (275.8) / (220.6)		
Izod Impact Strength (ASTM D256)	Condition A LW / CW	ft-lb/in (J/cm)			
	Condition E-48/50 LW / CW	ft-lb/in (J/cm)	7.90 / 7.30 (4.22) / (3.90)		
Compressive Strength (ASTM D695)	Condition A Flatwise	psi (MPa)	66,000 (455.1)		
Bonding Strength (ASTM D229)	Condition A	lb (kg)	2,300 (1,043.3)		
Shear Strength (ASTM D732)	Condition A Perpendicular	psi (MPa)	21,500 (148.2)		

TECHNICAL DATA BULLETIN

GRADE: NP510A

NEMA LI 1-1998 Grade: FR-4

U.L. LISTED: Y ²

TYPICAL PROPERTIES (continued)

		UNITS	VALUE		
			Thickness Tested		
			0.0625"	0.125"	0.500"
THERMAL PROPERTIES					
Temperature Index ¹ (<i>UL Bulletin 746b</i>)	Electrical / Mechanical	°C	130 / 140		
Coefficient of Thermal Expansion (<i>IPC-TM 650-2.4.24</i>)	X-axis / Y-axis	" / °C x10 ⁻⁶	10.0 / 13.0		
Tg by DMA		°C	130		
Flammability Vertical (<i>UL Bulletin 94</i>)	Condition A	Class	V-0		
ELECTRICAL PROPERTIES					
Dissipation Factor @ 1 MHz (<i>ASTM D150</i>)	Condition A	-			
	Condition D-24/23	-	0.032		
Relative Permittivity @ 1 MHz (<i>ASTM D150</i>)	Condition A	-			
	Condition D-24/23	-	4.80		
Breakdown Voltage (<i>ASTM D149</i>)	Condition A	kVolts	66		
	Condition D-48/50	kVolts	65		
Electric Strength (<i>ASTM D149</i>)	Condition A	Volts/mil (kV/cm)	630 (248.0)		
	Condition D-48/50	Volts/mil (kV/cm)	670 (263.8)		
Arc Resistance (<i>ASTM D495</i>)	Condition A	sec	130		

¹ This temperature is a recommendation only, and based upon experience in various applications. The maximum operating temperature is dependent upon the application and should be investigated prior to use.

² Only applies to thicknesses greater than 0.029".

This data, while believed to be accurate and based on reliable analytical methods, is for informational purposes only. The terms and conditions of the agreement under which it is sold will govern any sales of this product. Data supplied above are "typical values"; not to be considered "specification values".

To assure the material's performance is adequate for a specific application; customers should verify, independent of Norplex-Micarta, performance characteristics of interest.

It is the responsibility of the users of this information to make sure that they have the latest version of this TDB, and are urged to check with Customer Service or, preferably our web site, www.norplex-micarta.com, to determine if the information is the most current available.

Specification writers: Contact Norplex-Micarta for specification values before submission.

NP510A

TECHNICAL DATA BULLETIN

GRADE: NP510A

IEC 60893-3-2-EP GC 202

U. L. LISTED: Y

DESCRIPTION: NP510A is a woven glass fabric composite combined with epoxy resin system. It is engineered to provide NEMA grade FR-4 properties. This material contains bromine on the epoxy resin backbone. NP510A is certifiable to MIL-I-24768/27, Type GEE-F.

THICKNESS TESTED: 1.59mm, 3.18mm & 12.70mm

TYPICAL PROPERTIES

PHYSICAL PROPERTIES		UNITS	VALUE
Moisture Absorption (1.59mm) (IEC 60893-2/8.2)	Condition A	mg	8.30
Flexural Strength (1.59mm) (IEC 60893-2/5.1)	Condition A LW / CW	Mpa	480 / 390
Izod Impact Strength (12.7mm) (IEC 60893-2/5.4.3)	Condition A LW / CW	kJ/m ²	58 / 55
Charpy Impact Strength (12.7mm) (IEC 60893-2/5.4.2)	Condition A LW / CW	kJ/m ²	63 / 50
THERMAL PROPERTIES			
Flammability Vertical (1.59mm) (IEC 60893-2/7.2)	Condition A	Class	V-0
ELECTRICAL PROPERTIES			
Breakdown Voltage (3.18mm) (IEC 60893-2/6.1)	Condition A	kVolts	65
Electric Strength (1.59mm) (IEC 60893-2/6.1)	Condition A	kV/mm	25
Insulation Resistance (3.18mm) (IEC 60893-2/6.3)	Condition E-24/50; D-24/23	MΩ	3.33E+13

This data, while believed to be accurate and based on reliable analytical methods, is for informational purposes only. The terms and conditions of the agreement under which it is sold will govern any sales of this product. Data supplied above are "typical values"; not to be considered "specification values".

It is the responsibility of the users of this information to make sure that they have the latest version of this TDB, and are urged to check with Customer Service or, preferably our web site, www.norplex-micarta.com, to determine if information is most current available.

Specification writers: Contact Norplex-Micarta for specification values before submission.